



329.00 EUR  
incl. 19% VAT, plus [shipping](#)

- INTEL® Celeron-M Processor 1047UE + HM65 Chipset
- Support 1 \* DDR3 1066/1333MHz Single CH up to 8GB
- Support 1 \* Serial ATAIII (6Gb/s) Devices
- Support CFast card
- Support mSATA card (Share with Mini PCI-E)
- Support Mini PCI-E x 1
- 1 \* 24 bits Dual Channel LVDS header
- Support DVI-I Output
- Supports 2 \* Realtek RTL8111F-CG Gigabit LAN
- Support CPU Smart FAN

<b>Dimension (W*H*D)</b>	• 185 * 60 * 142 mm
<b>Construction</b>	• Aluminum housing
<b>Colors</b>	• Black / HBJC381F39-1047-B
<b>MB model</b>	• JNF39-1047 (3.5" SBC)
<b>CPU &amp; CHIP</b>	• INTEL® Celeron-M Processor 1047UE + HM65 Chipset
<b>BIOS</b>	• AMI 32MB SMT Flash ROM
<b>Memory</b>	• 1 * SO-DIMM slot (DDR3-1333/1600Mhz_Max 8GB)
<b>Storage Space</b>	• 1 * 2.5" SATA Device (Support SATA 6G / Max Height 9.5 mm) • 1 * m-SATA SSD Device (Mini PCI-E) • 1 * CFast card
<b>Display Interface</b>	• 1 * DVI-I • 1 * LVD-24 bits ( Internal pin header)
<b>Network</b>	• 2 * RJ45 (RTL8111F-CG Gigabit LAN) • WiFi (optional / JBC381F39W-1047-B)
<b>Audio</b>	• 2 * Line out • 1 * Mic in
<b>Front I/O Port</b>	• 2 * USB 2.0 • 2 * COM (Max 4 Ports)
<b>Rear I/O Port</b>	• 4 * USB 2.0
<b>Expansion Interface</b>	• 1 * Mini PCI-E (Full-size)
<b>Power Source</b>	• DC-12V Jack input • Adapter : AC_90~240V / DC_12V_5A / 60W
<b>Certification</b>	• EMC : CE , FCC • Safety : RoHS , ErP

---

• <b>Environment</b>	• Operating Temperature : 0 ~ 40■ • Storage Temperature : 0 ~ 60■ • Vibration During Operation : N/A • Shock During Operation : N/A
• <b>Mounting</b>	• Wall mounting Kits
• <b>Packing</b>	• Net Weight■2.2KG • Gross Weight■3.5KG • Color Box Dimension■250(W) x 118 (D) x 295 (H) mm