

329.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Slim NUC size Fanless system
- Intel® Bay Trail-M N2930 SoC Processor (1.83GHz, 7.5w)
- 1 \* SO-DIMM slot (Max to 8GB)
- 1 \* full size Mini PCIe slot for m-SATA Device
- Application: Panel PC, Commerce, Banking, Digital Signage, Gaming, Medical, POS/KIOSK, Industrial Automation, I.O.T, AIO

|                     |   |
|---------------------|---|
| • Dimension (W*D*H) | • 129 * 109 * 34 mm   |
| • Construction      | • Top cover & I/O plate –aluminum; Base- metal                                      |
| • Colors            | • Black / HBJC420U91-2930-B, HBJC420U91W-2930-B                                     |
| • MB model          | • JNU91-2930  |
| • CPU               | • INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz, 7.5w)                            |
| • BIOS              | • AMI UEFI  |
| • Memory            | • 1 * SO-DIMM slot (Max to 8GB)   |
| • Storage Space     | • 1 * full size Mini PCI-E slot for m-SATA Device                                   |
| • Display Interface | • 2 * HDMI  |
| • Network           | • 1 * RJ45 (Giga LAN)<br>• WiFi (HBJC420U91W-2930-B only)                           |
| • Audio             | • 1 * Line out  |
| • Front I/O Port    | • 1 * USB 3.0<br>• 1 * COM  |
| • Rear I/O Port     | • 2 * USB 2.0,<br>• 2 * HDMI<br>• 1 * GigaLAN,<br>• 1 * Line out<br>• 1 * 12V DC-in |
| • Expansion Slot    | • 1 * half size Mini PCI-E slot   |
| • Power Source      | • DC-12V Jack input<br>• Adapter : AC_90~240V / DC_12V_3A/36W                       |

---

|                    |   |
|--------------------|---|
| • Certification    | • EMC : CE , FCC<br>• Safety : RoHS , ErP   |
| • Environment      | • Operating Temperature : -10°C~60°C with air flow (mSATA)<br>• Storage Temperature : -20°C~80°C  |
| • Mounting Bracket | • Multiple use bracket (Wall/VESA/DIN Rail)   |
| • Packing          | • Net Weight■0.9KG<br>• Gross Weight■1.6KG<br>• Color Box Dimension■158(W) x 167(D) x 123.6(H) mm |