



529.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel Bay Trail-M N2930 (1.83GHz) Quad Core SoC Processor
- 2 * DDR3L 1333MHz SO-DIMM up to 8GB
- 1 * USB3.0, 1 * USB2.0, 2 * COM, 1 * GPIO, 1 * VGA
- 4 * GbE, expansion LAN Card * 4 ports (optional)
- Supports 12V DC jack on back panel for external power supply
- Provides DC-12V_5A_60W Adapter

| | |
|-------------------|---|
| Product Dimension | - 192(D) * 330(W) * 44(H) mm |
| Product Model | - HBJC141F9HGXX-29B |
| Model No | - JBC141F9HG04-29B - JBC141F9HG08-29B - JBC141F9HGW4-29B - JBC141F9HGW8-29B |
| MB Model | - JNF9HG-2930 / Mini-ITX |
| BIOS | - AMI 128 MB Flash ROM |
| CPU | - Intel® Bay Trail – M/D/I Processor (2930) |
| Memory | - 2 * SO-DIMM DDR3L 1333MHz up to 8GB |
| Expansion | - 1 * Mini-PCIE (Full size) - 1 * Mini-PCIE for mSATA (Full size) |
| Storage | - 2 * 2.5" SATA bay - 1 * mSATA (Full size) |
| Front I/O Port | - 1 * Power LED, 1 * HDD LED - 1 * USB 3.0, 1 * USB 2.0 - 2 * COM - 1 * GPIO (Optional) - 1 * VGA - 4 * GbE - 4 * Expansion LAN Card (Optional) |
| Rear I/O Port | - 1 * DC-in - 1 * GND Hold |
| Power Source | - Supports 12V DC input - Provides AC_90~240V / DC_12V 60W adapter |

| | |
|---------------|---|
| Accessory | <ul style="list-style-type: none"> - 1 * Power cord - 1 * DC-12V/5A/60W Adapter - 1 * User Manual - 1 * CD driver - 1 * Screw Pack |
| Packing | <ul style="list-style-type: none"> - Net Weight■ 1.6 KG - Gross Weight■2.6 KG - Color Box Dimension■ (W) x (D) x (H) mm |
| Temperature | <ul style="list-style-type: none"> - Operating within 0~50°C - Storage within -10~70°C |
| Certification | <ul style="list-style-type: none"> - EMC : CE , FCC , LVD - Safety : RoHS , ErP |
| Applications | <ul style="list-style-type: none"> - Industrial Control System - Networking Server System - Security Industry |
| Warranty | <ul style="list-style-type: none"> - 2 Year limited warranty |