

619.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel Apollo Lake-I SoC Processor (Default: E3940)
- Support 1* SO-DIMM DDR3L-1866MHz up to 8GB
- All-aluminum body, produced by casting process
- Operating Temperature: -40 ~ 70°C
- 9~36V DC-in (Phoenix terminal connector)

| | |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model | - JNF951T-E3940 |
| Model No. | - HBJC386F951T-3940B - HBJC386F951TW-3940B (WIFI) |
| BIOS | - AMI Flash ROM |
| CPU/Chipset | - Intel® Apollo Lake-I SoC Processor (Default: E3940) |
| Memory | - 1* SO-DIMM slots DDR3L-1866MHz up to 8GB |
| Storage | - 1* 2.5" SATA3 6Gb/s internal drive bay - 1* M.2 (M-key 2280) slot for SSD |
| Network | - 2* Intel I210-IT GbE - 1* Full-size mini-PCIE slot |
| Rear Panel I/O | - 4* USB3.0 - 2* RJ45 - 1* VGA - 1* HDMI - 1* Line out - 2* WIFI Antenna (HBJC386F951TW-3940B only) - 1* DC-in (3 Pin Phoenix terminal) |
| Front Panel I/O | - 1* Power SW + Power LED - 1* ATX & AT mode Switch - 1* SIM Card slot - 2* COM (RS232/422/485_ COM1 w/power) - 1* Power SW (2 PIN out) - 1* 16 bit GPIO (8-IN, 8-OUT w/isolated) - 2* RS485 (w/isolated) |
| Power Source | - Adapter: AC 90~240V input / DC12V-5A-60W - MB: Support 9~36V DC-in |

| | |
|-------------|-------------------------------------------------------------------------------------------------------|
| Compliance | – CE, FCC, LVD, RoHS, ErP Ready |
| Temperature | – Operating: -40 ~ 70°C – Storage: -20 ~ 70°C – Humidity: 90%, non-condensing |
| Dimensions | – 185 (W) x 142 (D) x 60 (H) mm |
| Packing | – Net Weight: 2.2KG – Gross Weight: 3.5KG – Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm |
| Warranty | – 2 Year limited warranty |