



369.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- HB368F21 !

- Intel Elkhart Lake SoC Processor
- 1\* DDR4 3200MHz SO-DIMM up to 32GB
- 2\* USB3.1 (Gen.2), 4\* USB2.0, 2\* RJ45, 1\* Audio (MIC + Line-out), 1\* Line-IN, 3\* DP, 2\* COM, 1\* GPIO
- 160.2\*106\*27 mm
- DC12V\_40W Adapter
- Support TPM2.0 (option)

Model	– HB368F21-6210-S (non-WiFi) – HB368F211-6210-S (WiFi)	
CPU/Chipset	– Intel® Elkhart Lake SoC Processor(N6210, TDP 6.5W)	
BIOS	– AMI Flash ROM	
Memory	– 1* DDR4 3200MHz SO-DIMM up to 32GB	
Network	– 2* Realtek RTL8119I GbE	
Graphics	– Intel® HD Graphics, shared memory – 3* DP (Max Resolution: 4096x2160@60Hz) – Support Triple Displays	
Storage	– 1* M.2 M-key (2242/2280, PCIe Gen.3 x2/SATA interface) support NVME – 32GB eMMC onboard (option)	
Expansion	– 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface) – 1* M.2 B-key (3042, USB3.0 interface)	
Rear Panel I/O	– 2* RJ45 – 1* DC in (Lockable)	
Front Panel I/O	– 1* Power button + Power LED – 4* USB2.0 – 1* Audio(Line out+MIC) – 1* Line in – 3* DP	
Internal Connector	– SIM Card Holder	

Power Source	- Adapter : AC 90~240V input / DC12V_40W output - MB : DC12~36V input
Compliance	- CE, FCC, LVD, RoHS, ErP Ready
Dimensions	- System: 160.2 (W) x 106 (D) x 27 (H) mm - Net Weight: 0.61KG: Gross Weight: 1.12KG
Temperature	- Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD) - Storage Temperature: -20 ~ 60° C - Humidity: 10% ~ 90% RH @40°C (non-condensing)
OS Support	- Windows 11, Linux